



FONDU TECHNOLOGY

Type (particle size)

Package size

Standard

CIMENT FONDU®	FAST&FONDU®	FONDULIT®	FONDUCRETE®	FONDAG®
Cement	Mortar (0/3)	Mortar (0/2)	Concrete (0/6.3)	Concrete (0/10)
25 kg	25/5 kg	25/5 kg	25 kg	25 kg
CE - NF				

APPLICATIONS

Faster setting for mortar/concrete	●				
Small sealinging works		●			
Urban furniture sealing		●		●	
Fixing posts		●		●	
Urban paving		●			
Paving		●		●	
Quick return to service works	●	●		●	●
Seaside works	●	●		●	●
Agricultural works	●	●		●	●
Works at cold temperature (to 0° C)	●	●	●	●	●
Works at cold temperature (to -10° C)	●			●	●
Works subject to abrasion				(●)	●
Works subject to erosion				(●)	●
Works subjected to impacts					●
Private house paving slabs				●	
Lintels				●	
Industrial paving slabs (depending on the work)				●	●
Filling		●			
Repair mortar		●			
Repair concrete				●	●
Work subject to heat < 500°C	●	●	●	●	●
Work subject to heat < 800°C			●	●	●
Work subject to heat > 800°C			●		●
Work subject to fire > 800°C			●		●
Work subject to fire < 1100°C			●		●
Work subject to fire < 1300°C			●		●
Barbecues			●		●
Ovens			●		●
Fireplaces			●		●
H ₂ S mini rehabilitation work		●		●	●
H ₂ S maxi rehabilitation work					●
H ₂ S maxi Gunning rehabilitation work					

● recommended (●) suitable